

---

# Protocol "D"

TCP/IP Protocol for controlling the dynamic routing engine

Fred Gleason

## Table of Contents

Overview .....	1
Connection Management .....	1
Exit .....	1
Ping .....	2
Information .....	2
List Destinations .....	2
List GPIs .....	2
List GPOs .....	3
List Nodes .....	3
List Sources .....	3
Subscribe Destinations .....	4
Subscribe GPIs .....	4
Subscribe GPOs .....	5
Subscribe Nodes .....	5
Subscribe Sources .....	5
Commands .....	5
Clear Audio Crosspoint .....	5
Clear GPIO Crosspoint .....	6
Set Audio Crosspoint .....	6
Set GPIO Crosspoint .....	6

## Overview

Messages to the DRouter dynamic routing service are by means of a TCP SOCK\_STREAM connection to TCP port 23883 on the host server.

Messages have the following general syntax:

*cmd-code* [*arg*] [ . . . ]**CR/LF**

*cmd-code*                      A single word, containing no whitespace, case-insensitive.

*arg*                              Zero or more arguments, delimited by a **TAB** character (ASCII 9).

**CR/LF**                              The ASCII character **CR** (13) followed by **LF** (10).

## Connection Management

Messages for managing connections to the service.

### Exit

**Exit**

Drop the TCP connection and end the session.

## Ping

### Ping

Causes the remote end to return a PONG message.

## Information

Messages for enumerating resources and getting system information.

## List Destinations

### ListDestinations

Return a list of records delinieating the currently available destinations, terminated by CR/LF. Each record contains the following fields, delimited by TAB (ASCII 9):

<i>DST</i>	The string DST.
<i>host-addr</i>	The IPv4 address of the parent node, in dotted-quad notation.
<i>slot</i>	The slot position number of the destination on the parent node (zero-based).
<i>host-name</i>	The host name of the parent node. Depending upon system configuration, this could be the name as programmed in the node or the name as reported via a DNS PTR lookup.
<i>stream-addr</i>	The IPv4 address of the stream configured to be received, in dotted-quad notation.
<i>dest-name</i>	The name of the destination.
<i>channels</i>	The number of channels capable of being received by this destination. Possible values include 1, 2 or 8.

## List GPIs

### ListGpis

Return a list of records delinieating the currently available GPIs, terminated by CR/LF. Each record contains the following fields, delimited by TAB (ASCII 9):

<i>GPI</i>	The string GPI.
<i>host-addr</i>	The IPv4 address of the parent node, in dotted-quad notation.
<i>slot</i>	The slot position number of the GPI on the parent node (zero-based).
<i>host-name</i>	The host name of the parent node. Depending upon system configuration, this could be the name as programmed in the node or the name as reported via a DNS PTR lookup.

---

*state*                      The state of the GPI lines, in the format `xxxxxx`.

## List GPOs

### ListGpos

Return a list of records delinieating the currently available GPOs, terminated by CR/LF. Each record contains the following fields, delimited by TAB (ASCII 9):

<i>GPO</i>	The string GPO.
<i>host-addr</i>	The IPv4 address of the parent node, in dotted-quad notation.
<i>slot</i>	The slot position number of the GPO on the parent node (zero-based).
<i>host-name</i>	The host name of the parent node. Depending upon system configuration, this could be the name as programmed in the node or the name as reported via a DNS PTR lookup.
<i>state</i>	The state of the GPO lines, in the format <code>xxxxxx</code> .
<i>name</i>	The name of the GPO entry.
<i>src-host-addr</i>	The IPv4 address of the source GPI node, in dotted-quad notation.
<i>src-slot</i>	The slot position number of the source GPI on the source node (zero-based).

## List Nodes

### ListNodes

Return a list of records delinieating the currently available nodes, terminated by CR/LF. Each record contains the following fields, delimited by TAB (ASCII 9):

<i>NODE</i>	The string NODE.
<i>host-addr</i>	The IPv4 address of the node, in dotted-quad notation.
<i>host-name</i>	The host name of the node. Depending upon system configuration, this could be the name as programmed in the node or the name as reported via a DNS PTR lookup.
<i>dev-name</i>	The LWRP device name.
<i>src-slots</i>	The number of source slot positions.
<i>dst-slots</i>	The number of destination slot positions.
<i>gpi-slots</i>	The number of GPI slot positions.
<i>gpo-slots</i>	The number of GPO slot positions.

## List Sources

### ListSources

Return a list of SRC records, delinieating the currently available sources, terminated by CR/LF. Each record contains the following fields, delimited by TAB (ASCII 9):

<i>SRC</i>	The string SRC.
<i>host-addr</i>	The IPv4 address of the parent node, in dotted-quad notation.
<i>slot</i>	The slot position number of the source on the parent node (zero-based).
<i>host-name</i>	The host name of the parent node. Depending upon system configuration, this could be the name as programmed in the node or the name as reported via a DNS PTR lookup.
<i>stream-addr</i>	The IPv4 stream address in dotted-quad notation.
<i>stream-name</i>	The name of the stream.
<i>stream-enabled</i>	The current state of the stream. 1 if enabled or 0 if disabled.
<i>channels</i>	The number of channels being carried by the stream. Possible values include 1, 2 or 8.
<i>block-size</i>	The number of PCM24 frames carried by each RTP packet. Possible values include 12 (Live Stereo), 60 (8 Channel Surround) and 240 (Standard Stereo/Mono).

## Subscribe Destinations

### SubscribeDestinations

Return a list of DSTADD records delinieating the currently available destinations, each record terminated by CR/LF (see the description of the DST message in the **ListDestinations** command for a breakdown of the supplied fields). Whenever a new destination is added, a corresponding DSTADD record will be sent, while changes to an existing destination will cause a DST record to be sent. Removal of a destination from the system will generate a corresponding DSTDEL record, containing the following fields:

<i>DSTDEL</i>	The string DSTDEL.
<i>host-addr</i>	The IPv4 address of the parent node, in dotted-quad notation.
<i>slot</i>	The slot position number of the destination on the parent node (zero-based).

## Subscribe GPIs

### SubscribeGpis

Return a list of GPIADD records delinieating the currently available GPIs, each record terminated by CR/LF (see the description of the GPI message in the **ListGpis** command for a breakdown of the supplied fields). Whenever a new GPI is added, a corresponding GPIADD record will be sent, while changes to an existing GPI will cause a GPI record to be sent. Removal of a GPI from the system will generate a corresponding GPIDEL record, containing the following fields:

<i>GPIDEL</i>	The string GPIDEL.
<i>host-addr</i>	The IPv4 address of the parent node, in dotted-quad notation.

*slot* The slot position number of the GPI on the parent node (zero-based).

## Subscribe GPOs

### SubscribeGpos

Return a list of GPOADD records delineating the currently available GPOs, each record terminated by CR/LF (see the description of the GPO message in the **ListGpos** command for a breakdown of the supplied fields). Whenever a new GPO is added, a corresponding GPOADD record will be sent, while changes to an existing GPO will cause a GPO record to be sent. Removal of a GPO from the system will generate a corresponding GPODEL record, containing the following fields:

GPODEL The string GPODEL.

*host-addr* The IPv4 address of the parent node, in dotted-quad notation.

*slot* The slot position number of the GPO on the parent node (zero-based).

## Subscribe Nodes

### SubscribeNodes

Return a list of NODEADD records delineating the currently available nodes, each record terminated by CR/LF. Subsequently, for each newly detected node, a corresponding NODEADD record will be sent, while changes to an existing node will cause a NODE record to be sent. Removal of a node from the system will generate a corresponding NODEDEL record with the following fields:

NODEDEL The string NODEDEL.

*host-addr* The IPv4 address of the node, in dotted-quad notation.

## Subscribe Sources

### SubscribeSources

Return a list of SRCADD records delineating the currently available sources, each record terminated by CR/LF (see the description of the SRC message in the **ListSources** command for a breakdown of the supplied fields). Whenever a new source is added, a corresponding SRCADD record will be sent, while changes to an existing source will cause a SRC record to be sent. Removal of a source from the system will generate a corresponding SRCDEL record, containing the following fields:

SRCDEL The string SRCDEL.

*host-addr* The IPv4 address of the parent node, in dotted-quad notation.

*slot* The slot position number of the source on the parent node (zero-based).

## Commands

Messages for changing the state of managed resources.

## Clear Audio Crosspoint

**ClearCrosspoint** *dst-host-addr dst-slot*

Clear the source to be received by an audio destination --i.e. mute the destination.

*dst-host-addr*                      The IPv4 address of the destination node, in dotted-quad notation.

*dst-slot*                              The slot position number of the destination on the parent node (zero-based).

## Clear GPIO Crosspoint

**ClearGpioCrosspoint** *gpo-host-addr gpo-slot*

Clear the source to be received by a GPO.

*gpo-host-addr*                      The IPv4 address of the GPO node, in dotted-quad notation.

*gpo-slot*                              The slot position number of the GPO on the parent node (zero-based).

## Set Audio Crosspoint

**SetCrosspoint** *dst-host-addr dst-slot src-host-addr src-slot*

Set the source to be received by an audio destination.

*dst-host-addr*                      The IPv4 address of the destination node, in dotted-quad notation.

*dst-slot*                              The slot position number of the destination on the parent node (zero-based).

*src-host-addr*                      The IPv4 address of the source node, in dotted-quad notation.

*src-slot*                              The slot position number of the source on the parent node (zero-based).

## Set GPIO Crosspoint

**SetGpioCrosspoint** *gpo-host-addr gpo-slot gpi-host-addr gpi-slot*

Set the source to be received by a GPO.

*gpo-host-addr*                      The IPv4 address of the GPO node, in dotted-quad notation.

*gpo-slot*                              The slot position number of the GPO on the parent node (zero-based).

*gpi-host-addr*                      The IPv4 address of the GPI node, in dotted-quad notation.

*gpi-slot*                              The slot position number of the GPI on the parent node (zero-based).