
Name

rd_deleteaudio — Rivendell Audio Store C Library Function

Synopsis

```
#include <rivwebcapi/rd_deleteaudio.h>
```

```
int RD_DeleteAudio(hostname[], username[], passwd[], ticket[],  
cartnumber, cutnumber, user_agent[]);
```

```
const char hostname[];  
const char username[];  
const char passwd[];  
const char ticket[];  
const unsigned cartnumber;  
const unsigned cutnumber;  
const char user_agent[];
```

Description

RD_DeleteAudio is the function to use to delete PCM/MPEG data from the audio store.

Table 1. RD_DeleteAudio function call fields

| FIELD NAME | FIELD TYPE | MEANING | REMARKS |
|------------|------------------|--|--|
| hostname | Character Array | Name Of Rivendell DB Host | Mandatory |
| username | Character Array | Rivendell User Name | Mandatory When NO Ticket Provided |
| passwd | Character Array | Rivendell User Password | Mandatory When NO Ticket Provided |
| ticket | Character Array | Rivendell Authentication Ticket | Mandatory When NO User/Password Pair Provided. |
| cartnumber | unsigned integer | Cart Number | Mandatory |
| cutnumber | unsigned integer | Cut Number | Mandatory |
| user_agent | Character Array | User Agent Value put into HTTP request | Optional (default is Rivendell-C-API/x.x.x) |

RETURN VALUE

On success, zero is returned.

If a server error occurs a -1 is returned. If a client error occurs a specific error number is returned.

ERRORS

400 Missing Cart Number / Cut Number Error.

403 User Authentication Error.

404 No Such Cut or Invalid Permissions.

nnn Unknown Error Occurred.